

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 December 2001 (27.12.2001)

PCT

(10) International Publication Number
WO 01/98753 A1

(51) International Patent Classification⁷: **G01N 17/02**

(21) International Application Number: PCT/GB01/02543

(22) International Filing Date: 8 June 2001 (08.06.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0015349.4 23 June 2000 (23.06.2000) GB

(71) Applicant and

(72) Inventor: **ATHERTON, Eric** [GB/GB]; 83 Wroslyn Road, Freeland, Witney, Oxfordshire OX8 8HL (GB).

(74) Agents: **DOWNING, Michael, Philip** et al.; Fry Heath & Spence, The Old College, 53 High Street, Horley, Surrey RH6 7BN (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CORROSION MONITORING



(57) Abstract: A corrosion monitor comprising electronic circuitry arranged such that DC current flowing between two electrodes is reduced to essentially zero, while allowing any naturally occurring AC current noise to flow unhindered and be monitored by the instrumentation. The two electrodes consist of one inert reference electrode, and one electrode constructed of the material to be monitored (the working electrode). Even though the two electrodes will have different galvanic potentials, by reducing the DC current to zero the electronic circuitry is able to avoid galvanic effects. Furthermore, the voltage potential can be monitored between the inert reference electrode, and a third electrode also constructed of an inert material. As corrosion activity occurs on the working electrode, both current noise and voltage noise may then be monitored simultaneously.

WO 01/98753 A1